

## HIGH PERFORMANCE EPOXY 100 PARTS A & B

## SUPER HIGH GLOSS EPOXY SURFACE SEALER



**HIGH PERFORMANCE EPOXY 100 IS A SUPER HIGH GLOSS EPOXY SURFACE SEALER FOR ALL INTERIOR LATERAL CONCRETE SURFACES, OVERLAYS, METALLICS, COUNTER TOPS, CONCRETE FLOORS & CHIP BROADCAST SYSTEMS.**

### PRODUCT HIGHLIGHTS

- Super high gloss clear finish, with a clear wet appearance.
- Self leveling.
- **Resistant:** Stain resistant, blush resistant, solvent resistant.
- **Fast cure:** 24 hours for foot traffic, and 72 hours for wheel traffic.
- Available in a 2 part kit

### USES

High Performance Epoxy 100 is recommended as a high gloss finish sealer for interior lateral concrete surfaces including overlay and solid concrete countertops, concrete floors, and concrete overlays. Use Epoxy Top 100 as a base for chip broadcast systems and metallic pearl effects.

### QUICK LOOK: PART A

**Type:**

**Toxicity:** Harmful if swallowed

**VOC's:** Low

**Flammability:** Non-Flammable

**Composition:**

**Color:**

**Odor:**

**Coverage:** 80-100sq.ft. per gallon @ 16-18mLs

*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.



### QUICK LOOK: PART B

**Type:**

**Toxicity:** Harmful if swallowed, or inhaled

**VOC's:** Low

**Flammability:** Non-Flammable

**Composition:**

**Color:**

**Odor:**

**Coverage:** 80-100sq.ft. per gallon @ 16-18mLs

*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.

